



V-Blast and R-Blast

Brown Aluminum Oxide

MATERIAL SAFETY DATA SHEET

EFFECTIVE DATE: 01-01-2012

GMA Industries
38127 Ecorse Road
P.O. Box 74037
Romulus, MI 48174-0037
734-595-7300

I. IDENTIFICATION

Product Name: V-Blast

Product Name: R-Blast

Chemical Name: Brown Fused Aluminum Oxide

Chemical Name: Brown Aluminum Oxide

Formula: Al₂O₃

Formula: Al₂O₃

II. INGREDIENTS

INGREDIENTS	CAS NO.	% W	ACGIH TLV	OSHA PEL		CARCINOGENIC
				TWA	RWA	
Aluminum Oxide – Al ₂ O ₃	1344-28-1	92.0 – 96.5	10 mg/m ³	15 mg/m ³	5 mg/m ³	No
Titanium Dioxide – TiO ₂	13463-67-7	1.0 – 4.0	10 mg/m ³	15 mg/m ³	5 mg/m ³	No
Silicon Dioxide – SiO ₂	7631-86-9	0.0 – 1.0	80 mg/m ³	80 mg/m ³	5 mg/m ³	No
Iron Oxide – Fe ₂ O	1309-37-1	0.1 – 1.5	5 mg(Fe)/m ³	10 mg/m ³	5 mg/m ³	No
Impurities, other total oxides (trace amounts)		<1.0				

III. PHYSICAL DATA

Vapor Pressure:	0	Specific Gravity (water =1):	3.95
Vapor Density:	N/A	Percent Volatile:	0
Evaporation Rate:	0	pH:	Neutral
Percent Solid (by weight):	100	Appearance:	Brown granular
Solubility in Water:	Insoluble	Odor:	None

IV. FIRE & EXPLOSION HAZARD DATA

Flashpoint:	None	Flammable Limits:	None
Unusual Fire or Explosion Hazards:	None	Special Fire Fighting Procedures:	None

V. STABILITY & REACTIVITY DATA

Chemical Stability:	Stable	Incompatibility:	None
Hazardous Polymerization:	Will not occur	Hazardous Decomposition Products:	None
Thermal Decomposition:	None	Dangerous Reactions:	None
Conditions to avoid:	None		

VI. POTENTIAL HEALTH EFFECTS

Emergency Overview: Dust irritating to eyes and respiratory tract.

Eyes: Mechanical eye irritant, many cause tearing and redness.

Skin: Mechanical skin irritant, prolonged contact many cause abrasions, redness or itching.

MATERIAL SAFETY DATA SHEET

GMA V-Blast and R-Blast – Brown Aluminum Oxide

EFFECTIVE DATE: 01-01-2012



Ingestion:May cause nausea and vomiting. No long-term effects are anticipated.
Inhalation:Dust maybe slightly irritating to respiratory tract. May cause coughing/shortness of breath.
Target Organs:Eyes, skin and respiratory system.
Effects of Exposure:.....May include persistent cough or shortness of breath.
Chronic Exposure:N/A

VII. EXPOSURE & PERSONAL CONTROLS

Plant Controls:Provide sufficient mechanical ventilations to reduce airborne concentrations and minimize exposure. Maintain employee exposure to below applicable permissible limits.
Hygiene Measures :Do NOT inhale dust/smoke/mist. Avoid contact with eyes or skin. Wash hands before eating.
Sensitization:.....N/A
Protection in Workplace:If concentrations of airborne dust exceed limits listed in Section III, Exposure Limits, follow the OSHA respirator regulations found in 29CFR 1910.134.
Eye Protection:Avoid eye contact. To minimize the risk of eye injury, always wear appropriate protective glasses or chemical safety goggles.
Skin Protection:.....Avoid skin contact. Wear appropriate protective clothing to minimize risk of abrasion or skin irritation.

VIII. FIRST AID MEASURES

Eyes:.....Flush eyes with large amounts of water. If symptoms persist, seek medical attention.
Skin:Wash effected area with soap & water. If symptoms persist, seek medical attention.
Inhalation:Remove affected person to fresh air. If symptoms persist, seek medical attention.
Ingestion:In the unlikely case of ingestion, leave the decision to induce vomiting to qualified medical personnel so as to avoid aspirating into the lungs. Seek immediate medical attention.

IX. FIREFIGHTING MEASURES

Flammable/Combustible Properties: None
Extinguishing Media:.....Extinguisher suitable for ordinary combustible materials, Class A extinguishing agents.
Special Fire Fighting Procedures:.....None

X. ACCIDENTAL RELEASE MEASURES

Personal Safety Precautions:Avoid creating dust.
Environmental Precautions:Ensure that materials are properly disposed of.
Clean-up Measures:Collect spilled materials by means of vacuuming or sweeping and place in a suitable container.

MATERIAL SAFETY DATA SHEET

GMA V-Blast and R-Blast – Brown Aluminum Oxide

EFFECTIVE DATE: 01-01-2012



XI. HANDLING & STORAGE

Handling: Avoid contact with eyes or skin. Wash hands before eating. Prevent the formation of dust. Handle with adequate ventilation.

Storage: Use normal storage practices. Store in original containers in a well ventilated area. Keep containers tightly sealed. Avoid stacking more than two high.

XII. ACCIDENTAL RELEASE MEASURES

Solid or chemical waste generators must determine if their discarded wastes are classified as a hazardous waste. U.S EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local waste regulations to ensure complete and accurate classification. Generally speaking, Brown Fused Aluminum Oxide, in and of itself, has NOT been classified as hazardous. Elements of the work piece being prepared can affect whether the spent oxide is hazardous. Check with your aluminum oxide source for accurate details.

XIII. TRANSPORTATION INFORMATION

U.S. DOT: This product is not regulated by USDOT as a hazardous material, no placard required to move this material.

XIV. REGULATORY INFORMATION

TSCA: Aluminum Oxide is listed on the TSCA inventory under CAS# 1344-28-1.

RCRA: Aluminum Oxide is not classified as a hazardous material under RCRA or its regulations, 40 CFR 302.

CERCLA: Aluminum Oxide is not classified as a hazardous substance under CERCLA regulations, 40 CFR 302.

SARA: Aluminum Oxide is not an extremely hazardous substance in Section 302 and is not a toxic chemical subject to the requirements of 313.

DISCLAIMER

The information in this MSDS was obtained from sources that we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied regarding accuracy or correctness. The conditions or methods of handling, storage use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

Abbreviations

CAS No.– Chemical Abstracts Service Registry Number

% W – Percent by weight

ACGIH TLV – American Conference of Governmental Industrial Hygienists Threshold Limit Values

OSHA PEL – Occupational Health and Safety Administration Permissible Exposure Limits

TWA – Total Weighted Average

RWA– Total Respirable Average

EPA – Environmental Protection Agency

DOT – Department of Transportation

TSCA – Toxic Substances Control Act

RCRA – Resource Conservation and Recovery Act

CERCLA – Comprehensive Environmental Response, Compensation, and Liability Act

SARA – Superfund Amendments and Reauthorization Act

N/A - Not Applicable

N/D - Not Determined